



PATTERN	SIZE	OD inches	OD mm	SECTION inches	SECTION mm	TREAD inches	TREAD mm	DESIGN RIM	RIM RANGE	RPM @ 100 MPH
R 1	700-18	32.1	815	8.8	224	5.4	137	5.0	5.0-7.0	629
	700-19	32.9	837	8.9	225	5.1	130	5.0	4.5-6.5	612
	550/600-18	30.1	765	6.9	175	4.3	109	4.5	4.5-6.5	670
R 5	450-15	24.0	610	5.6	142	3.5	90	4.0	3.0-4.5	840
	500-15	24.8	630	6.8	173	3.8	96	4.5	3.0-5.0	824
	550-15	25.8	655	7.1	180	4.2	107	5.0	3.5-5.5	768
	600-15	26.6	676	7.7	197	4.6	116	5.5	4.0-6.0	755
	650-15	27.4	696	8.4	214	4.9	124	6.0	4.5-6.5	746
	550-16	27.1	688	7.0	178	4.2	106	5.5	4.5-6.0	745
	600-16	27.9	708	7.8	198	4.8	121	5.5	4.5-6.0	723
	650-16	28.9	735	8.3	201	4.8	121	6.0	4.5-6.5	698
	700-16	29.1	740	8.8	224	4.9	125	7.0	5.5-7.5	692
	550-17	28.1	713	6.5	165	3.8	97	4.0	4.0-6.0	718
700-17	30.2	676	8.3	210	4.5	114	6.0	5.0-7.0	668	
3 & 5 STUD	500-19 (5 STUD)	29.6	753	6.2	157	3.7	93	4.0	3.5-5.5	680
	600-19 (5 STUD)	31.0	787	6.9	175	4.3	109	4.5	4.0-6.0	651
	650-19 (5 STUD)	31.6	803	7.8	198	4.6	117	5.0	4.0-6.0	638
	4.50-19 (3 STUD)	28.2	717	5.5	140	3.6	91	4.0	3.5-4.5	715
POST HISTORIC CR65	175/550-13	21.9	555	9.1	231	6.8	172	8.0	5.5-8.0	923
	475/1000-13	23.3	593	9.4	239	7.1	181	8.0	5.5-8.5	864
	475/1150-13	22.8	578	10.8	274	8.3	211	9.0	7.0-10.0	886
	600/1200-13	25.2	640	12.3	312	9.4	239	10.0	9.0-11.0	800
	600/1350-13	25.0	635	13.8	351	10.8	274	12.0	11.0-14.0	807
	475/1000-15	24.7	627	9.8	249	7.1	181	8.0	6.0-9.0	817
	600/1200-15	26.6	627	12.4	314	9.4	240	10.0	9.0-11.0	759
	525/1050-15	25.7	652	10.5	266	8.0	207	8.5	7.5-10.0	786
L Series CR 48	450L15	24	609	6.1	156	6.1	156	5.0	3.5-6	841
	600L16	27.8	708	7.9	201	4.8	122	5.0	5-7	724
	650L16	28.7	729	8.9	130	5.1	122	7.0	5.5-7.5	703



PATTERN	SIZE	OD inches	OD mm	SECTION inches	SECTION mm	TREAD inches	TREAD mm	DESIGN RIM	RIM RANGE	RPM @ 100 MPH
M SECTION CR65	450 M13	21.7	552	6.7	172	4.9	124	5.5	4.0-7.5	920
	525 M13	23.2	590	8.3	210	5.8	148	5.5	5.0-8.0	868
	550 M13	23.7	602	9.9	251	6.9	175	8.0	6.0-9.0	851
	550 M14	25.0	635	9	228	5.9	150	7.0	5.5-8.0	805
	500 M15	25.5	648	8.7	221	6.0	152	7.5	5.5-8.0	791
	550 M15	26.0	660	9.5	241	6.5	165	8.0	6.0-8.5	776
	600 M15	27.0	686	10.7	271	7.0	178	8.5	7.0-9.0	747
	650 M15	28.0	711	11.6	295	8.0	203	9.0	7.5-10.	720
L SECTION CR 65	500 L10	19.6	498	6.5	165	4.7	119	4.5	3.5-5.5	1029
	450 L12	21.3	540	6.9	175	4.7	119	5.0	4.0-7.0	968
	450 L13	22.1	560	6.6	167	4.5	115	5.0	3.5-7.0	915
	550 L13	23.9	608	7.8	199	5.0	127	5.5	4.0-7.0	844
	550 L14	24.8	631	7.8	199	5.0	127	5.5	4.0-6.5	812
	550 L15	24.8	631	7.4	187	4.7	119	6.0	4.0-7.0	812
	550 L15 *	25.9	659	8.0	204	5.0	127	6.5	4.0-7.0	777
	600 L15	26.9	684	8.8	224	5.3	135	7.0	5.0-7.50	749
	650 L15	27.8	706	9.4	239	5.6	142	7.5	5.5-8.0	726
	700 L15	27.8	706	10.4	265	6.6	167	8.0	6.5-9.0	719



3 & 5 STUD



CR 48



R 5



R 1



CR 65



CR 82